



### Characteristics:

Lockstitch machine, on which the sewing head and the presser foot can be lifted 12 cm/5 inches.

Armlength: HECTOR standard 60 cm/24 inches  
HECTOR long 100 cm/40 inches

### Standard equipment:

Dial to preset stitch length

Dial to preset number of stitches.

The circle diameter or the length of the line is set by means of an allen key.

Preset backtacking

Thread trimmer

Position light

Double table

Bobbin Winder

Safety Start with twin buttons

### Optional equipment:

Manual indexer model CESAR.

Computerized indexer model INGEMAR.

UV-light

### Electrical supply:

220 V 50/60 cycle

Other voltage on request.

### Compressed air:

6 bar or 90 p.s.i.

### Size incl. table:

1,8x1,2 m/70x47 inches

### Export packing:

WxLxH 1,0x1,3x1,5 m/40x51x60 inches

Weight: 270 kg/600 lbs.

### Example of cycle time:

4 seconds for a circle with a diameter of 10 mm (3/8 inches) using 18 stitches (2 turns - 6 stitches/each + overlapping and backtacking).

### Design and construction:

In accordance with the health and safety requirements of the European Communities.

### Patterns:



Min. 4 mm/0.2 inch – max. 25 mm/1 inch